

MAINTENANCE GUIDE FOR DESIGNER FLOORS

Regular cleaning is more beneficial and cost effective than occasional cleaning.

INITIAL SITE CLEAN FOR ALL EPOXY FLOORS

Remove all debris, dirt and dust off the floor. Vacuum clean and/or static (dust control) mop the floor thoroughly then auto scrub with a neutral detergent. It is recommended the use of felt pad under furniture if using a vacuum use the brush settings.

DOMESTIC AREAS

Regular cleaning (recommended twice weekly)

- Sweep with a static (dust control) mop
- Mop with neutral detergent or vinegar.
- Dry mop afterwards

Occasional Maintenance (Yearly) if required

- Sweep with a static (dust control) mop
- Strip floor of polish using stripper and red or white pad on a polyvac
- Auto scrub to remove stripper or use wet vac
- Rinse with clean water, allowing to dry
- Apply 3 – 4 coats polish

Recommend Polish: Research Glazer

<http://www.oateslaboratories.com/Category/research-products/hard-floor-care/sealers/glazer#>

Note

- ✓ The maintenance system requires the installation of an effective barrier matting system
- ✓ Cleaners and detergents should be diluted as per the manufacturers' instructions
- ✓ Only use neutral floor cleaning products. Do not use household detergents.
- ✓ Always follow the Health and Safety guidance provided.



Winner Flooring Magazine - 2007 "Most Innovative Product for Australia & NZ".
Environmentally friendly, non-slip, non-toxic, durable designer luxury floors at affordable prices.

Internet: www.aasexyfloors.com.au



AAA-2010
GECA 23-2005-
ARCHITECTURAL
& PROTECTIVE COATINGS

INITIAL SITE CLEAN FOR ALL EPOXY FLOORS

Remove all debris, dirt and dust off the floor. Vacuum clean and/or static (dust control) mop the floor thoroughly then auto scrub with a neutral detergent. It is recommended the use of felt pad under furniture if using a vacuum use the brush settings

COMMERCIAL AREAS

Regular cleaning (recommended once weekly)

- Sweep with a static (dust control) mop
- Mop with neutral detergent
- Buff using a white or red pad on a polyvac

Periodic cleaning (Quarterly)

- Auto scrub with neutral detergent
- Rinse with clean water, allowing to dry
- Apply 2 – 3 coats polish depending on wear

Occasional Maintenance (Yearly)

- Sweep with a static (dust control) mop
- Strip floor of polish using stripper and red or white pad on a polyvac
- Auto scrub to remove stripper or use wet vac
- Rinse with clean water, allowing to dry
- Apply 3 – 4 coats polish We recommend Research Glazer and Filmstar.
- <http://www.oateslaboratories.com/Category/research-products/hard-floor-care/sealers/glazer#>

Note

- ✓ The maintenance system requires the installation of an effective barrier matting system
- ✓ Cleaners and detergents should be diluted as per the manufacturers' instructions
- ✓ Only use neutral floor cleaning products. Do not use household detergents.
- ✓ Always follow the Health and Safety guidance provided.



Winner Flooring Magazine - 2007 "Most Innovative Product for Australia & NZ".
Environmentally friendly, non-slip, non-toxic, durable designer luxury floors at affordable prices.

Internet: www.aasexyfloors.com.au



AAA-2010
GECA 23-2005-
ARCHITECTURAL
& PROTECTIVE COATINGS